



**MONTPELIER MOTOR SPEEDWAY**  
**Milkman Promotions LLC**  
700 S. Jefferson Street / Montpelier, IN 47359

### 2026 STREET STOCK RULES

#### DISCLAIMER:

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events at Montpelier Motor Speedway, and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. No expressed or implied warranty of safety shall result from publications of or compliance with these specifications and/or regulations. They are intended as a guide for the conduct of the sport, the construction of a racecar, and are in no way a guarantee against injury or death to a participant, spectator, or official.

#### GENERAL SAFETY GUIDELINES:

1. A **four-post roll cage** must be installed, with a minimum of three (3) door bars on the driver's door and a minimum of two (2) bars on the passenger door. Roll bar construction must adhere to minimum limits of 1 ½" O.D. and .090 thickness (round).
2. A **steel plate** must be welded to the driver's door bars to protect against intrusion. Minimum thickness of this plate shall be 1/8".
3. **Drive shaft loop** is mandatory and must be installed 6-8 inches behind the transmission tail shaft. Chains are not permitted for this purpose.
4. A minimum of three (3) bars must be installed in the **windshield opening area**, of 3/8" minimum thickness. A steel mesh screen is optional.
5. All drivers must wear a **flame-retardant driving suit**. If the driving suit is a two-piece design, both the top and bottom pieces must be worn at the same time.
6. **Nomex driving gloves** are mandatory while Nomex shoes and Nomex underwear are highly recommended.
7. A full shield racing **helmet** is required with a Snell rating of SA2015 or newer.
8. An approved **2.5 fire extinguisher**, in working order, may be securely and safely mounted with-in reach of the driver.
9. **Driver compartment area** must be fully enclosed with a complete floorboard. A solid firewall must be placed between the driver and engine compartment, and between the driver and fuel cell. Loose objects and/or added weight will not be allowed in the driver compartment.
10. SFI approved 5-point **racing harness (belts)** is mandatory – which includes a crotch/submarine belt and must be securely fastened to the roll cage with nuts/bolts and washers. All belts must be dated and no more than 3-years old.
11. A designed-for-racing **high back aluminum seat** is mandatory. Full Containment Seats are highly recommended.
12. **Window nets**, of the quick release system design, are optional.
13. **Mirrors** are not permitted.
14. **Batteries** must be securely fastened. If battery is inside the driver compartment, it must be boxed, covered and fully secured.
15. Any **weight** added to the car must be securely mounted using a minimum of two (2) ½" bolts through the weights and secured with wire. The added weight(s) must be painted white and have your car number clearly painted on them. If the added weight falls off during an event, the car is subject to being immediately disqualified for the remainder of that night's event.
16. A **lifting hook**, fully capable of lifting the weight of the car, must be securely attached to the frame at both the front and rear of the car and must be easily accessible by tow truck operator.
17. **Fuel cell** is mandatory.

#### CAR CONSTRUCTION GUIDELINES:

1. **Engine** must be cast iron block, engine can be setback no further than the centerline of the number one spark plug with the center of the ball joint. Cast iron **heads** are mandatory.
2. A single **gauge legal 500 cfm 2-barrel carburetor with unaltered choke horn** is required.
3. **Quick-change** rear ends are permitted, must have steel axle tubes.
4. Minimum **weight** shall be 3200 pounds (with driver, at the end of the race).
5. **Suspension mounting locations must remain stock, after market upper a-arm mounts allowed.** Tubular upper a-arms allowed, must have cross shaft. No three-link suspension, no J-bars.
6. **Tires** are limited to 8", and must be D.O.T. 60/70, no racing tires., with a maximum 8" wheel width. DOT Racing tires, like American Racer are **not permitted**.
7. Chassis must be full stock **frame**, with a minimum 108" wheelbase. Uni body chassis allowed, must be tied with minimum 2"x2" tubing.
8. **Rear spoiler** is permitted with up to 8" of surface height measurement.
9. The **body** must be stock appearing – no wedged-type bodies. The rear end must be enclosed fully between the rear fenders and from the top of the frame rails to the deck.
10. Racing **transmissions** are permitted. Reverse mount starters are permitted. Rear engine driven fuel and/or power steering pumps are not permitted. No ball spline transmissions.